



研域  
YENOTEK

深圳市汉智星科技有限公司

## Q250M3 VER:1.0A 规格表



Q250M3 VER:1.0A 正面图



Q250M3 VER:1.0A IO 图



Q250M3 VER:1.0A 侧面图

保存期限：三年

表单编码：QR-HZX-PD-004 (A0)



Product model	Q250M3 VER:1.0A(I210AT)
Processor	6th/7th/8th/9th Celeron/Pentium/Core™ i3/i5/i7 processors supporting the LGA1151 architecture, Note: Support 6/7/8/9 generation 95W CPU
Chipset	Intel Q250 high-speed chipset
Internal memory	2 * DDR4 DIMM slots for dual-channel 2133 MHZ memory, 2400 MHZ memory, and 2666 MHZ memory, with a maximum capacity of 64GB Integrated Intel® HD Graphics controller with 1*VGA port and 1*HD OUTPUT1.4 port
Display	1*VGA and 1*HD OUTPUT1.4 Supports single display, dual display mode, and extended mode
Network	2* Intel I210AT Gigabit network adapter, supporting network wake up and PXE functions
Store	4* SATA3.0 hard disk interface,SATA transmission speed up to 6Gbps
	1* MSATA interface, support Intel protocol SSD, transmission rate up to 6Gbps
	1* M.2 slot, supporting the M.2 2280 PCIE x4/SATA adaptive standard SSD
Tone frequency	Onboard ALC888S high fidelity audio controller, support Mic, Line out, line-IN
Expansion slot	1 * PCIE x16 slot
	1 * PCIE x4 slot
	2* PCI slot
I/O ports on the backplane	1* PS/2 keyboard and mouse interface
	1 x VGA display port
	1*HD OUTPUT display interface



	2* RS232 serial port (COM1/2 supports 5V/12V live function, COM1/2 supports RS485/422 function)
	2* RJ45 Gigabit network interface
	2* USB 2.0 port
	4* USB 3.0 interface
	1*Line out interface (green), 1* Mic interface (red), 1* Line-IN interface (blue)
Built-in I/O interface	1* PS/2 keyboard and mouse interface 1*6pin row pin and UK1 signal
	1* JVGA port 1*12pin pin row, same signal as DB15
	4 x RS232 serial port 2 x 5pin row pins
	1* front audio interface 2*5pin row pins
	4* USB 2.0 port 2*5Pin row pins
	1*USB2.0 port USB TYPE-A
	1* TPM port 2*8pin row pins
	1* Front panel function buttons and indicator ports 2*5pin row pins
	1*LPT 2*13 pin row
	1* 24pin ATX power input interface
	1* 8pin ATX power input interface
Fan interface	1*4pin CPU intelligent fan interface, 3* 4pin system intelligent fan interface
BIOS	64Mb Flash ROM
Operating system	Windows 7 / 10 / Linux
Guard dog	Support hardware reset function (256 level, 0~255 seconds)
Power supply type	ATX power input
Operating	0°C to 60°C



研 域  
YENOTEK

深圳市汉智星科技有限公司

temperature	
Storage temperature	-20°C to 70°C
Working humidity	5%-95% relative humidity, no condensation
dimension	245mm * 220mm(mATX)

### 订购信息：

No.	Model	Processor	Chipset	Memory	VGA	HD OUTPUT	LAN	USB	COM	RS485/RS422	Power
1	Q250M3 VER:1.0	LGA1151	Q250	2*DDR4	1	1	2*I211AT	11	6	2	ATX
2	Q250M3 VER:1.0(I210AT)	LGA1151	Q250	2*DDR4	1	1	2*I210AT	11	6	2	ATX