



研域工控
YANYU GONGKONG

ITX-B683_I522L VER:1.0 (6300U)



ITX-B683_I522L VER:1.0 主板正面图



ITX-B683_I522L VER:1.0 主板 IO 图



ITX-B683_I522L VER:1.0 主板侧面图

Product model	ITX-B683_I522L VER:1.0 (6300U)
processor	Integrated Intel®I5-6300U 2.4GHz dual-core quad-thread processor,TDP 15W
	Compatible with Intel® Skylake-U/Kabylake-U Pentium/Celeron/I3/I5/I7 low power processors
Chipset	SOC
Internal memory	2 * DDR4 SODIMM slots, supporting 2133 MHZ memory and a maximum of 32GB memory
Display	<p>Integrated Intel®HD Graphics S520, support DirectX 12, OpenGL 4.5, support 4K</p> <p>The maximum resolution supported by the 1 x VGA port is 1920X1200@60Hz</p> <p>1*HD OUTPUT1.4 port, the highest resolution supported is 4096X2304@24Hz</p> <p>1* Supports dual-channel 24bit LVDS interface</p>
	1*EDP interface, and LVDS interface to choose one of the two through the jump
Network	2* Intel WGI210AT Gigabit network adapter, supporting network wake up and PXE functions
Deposit	<p>1* SATA3.0 hard disk interface, transmission speed up to 6Gbps</p> <p>1* MSATA slot, support Intel protocol SSD, transmission speed up to 6Gbps</p> <p>1* M.2 slot, supporting M.22280 NVMEPCIE X4 or SATA SSDS</p> <p>Note:MSATA and TPM-4COM are optional. Four serial ports can be extended by TPM-4COM. The default port is MSATA</p>
Tone frequency	Integrated ALC888S 7.1+2 channel high fidelity audio controller, support MIC, Line_out, power amplifier



	Support power amplifier 2 Ω 5W speaker
Expansion Slot	1* Mini-PCIE slot, supporting WIFI/4G module
I/O ports on the backplane	2* USB3.0 port 1* HD OUTPUT port 1 x DB15 VGA port 2* RJ45 Gigabit network interface 1*Line-out(green), 1*MIC(red) 1*DC12V power supply Supports 12V power input and output
Built-in I/O interface	1* JVGA1 Interface 1*12pin(same signal as DB15) 1* JHD OUTPUT interface 2*8pin(same signal as HD OUTPUT interface) 1* LVDS interface 2*15pin, support dual channel 24bit 1* EDP interface (yellow) 2*15pin, with LVDS for one of two via jump 1* LVDS backlight power supply interface 1*6pin 2* RS232 serial interface, where COM1 supports 9pin live, COM2 supports RS485/422 function 6* USB2.0 interface 2*5pin 1* front audio interface 2*5pin 1* Front panel switch button and indicator port 2*5Pin 1* hard drive power port 1*4pin 1* power amplifier interface 1*4pin 1* LPT print interface 2*13pin 1* PS/2 keyboard and mouse interface 1* 4pin DC power interface (12V input/output power interface) 1* SIM card slot
Fan interface	1*4pin CPU intelligent fan interface, 1*4pin system fan interface
GPIO	Supports four input/output GPIO

BIOS	64Mb Flash ROM
Guard dog	Support hardware reset function (256 level, 0~255 seconds)
Power supply type	Adopts DC 12V power supply
Operating system	Windows 7 , Windows 10 , Linux
Operating temperature	-10°C to 60°C
Storage temperature	-20°C to 70°C
Working humidity	5%-95% relative humidity, no condensation
Dimension	170mm x 170mm

订购信息

NO.	Model	Processor	Frequency	Memory	VGA	HD OUTPUT	LVDS	EDP	LAN	USB	COM	485/422	Power
3	ITX-B683_I522L VER:1.0(6300U)	I5-6300U	2.4G	2*SODDR4	1	1	2ch/24Bit	1	2*210AT	8	2	COM2	DC12V