



研 域
YENTEK

深圳市汉智星科技有限公司

ITX-B75M1 VER:1.0 规格表



ITX-B75M1 VER:1.0 正面图



ITX-B75M1 VER:1.0 IO 图



ITX-B75M1 VER:1.0 侧面图

Product model	ITX-B75M1 VER:1.0
processor	Supports LGA1155 architecture 2th/3th Intel Celeron/Pentium/Core i3/i5/i7 processors
chipset	Intel Z77/B75 high-speed chipset
memory	1 x DDR3 DIMM slot, supporting 1066mhz, 1333mhz, or 1600 MHZ, and a maximum of 8GB
reveal	Integrated Intel® HD Graphics Graphics controller 1 x VGA port 1*HD OUTPUT1.4 port Supports single display mode, dual display mode, and extended mode
network	1*Intel I211AT Gigabit network adapter, supporting network wake up and PXE functions 1*Intel I219V Gigabit network adapter, supporting network wake up and PXE functions
store	2*SATA2.0 hard disk interface,SATA interface transmission speed up to 3Gbps 1*MSATA SSD interface, transmission speed up to 6Gbps
Audio frequency	Integrated ALC888S high fidelity audio controller, support Mic, Line out
Expansion slot	1*PCIE2.0 x16 The 1*M.2 supports WiFi
I/O ports on the backplane	1*PS/2 keyboard and mouse interface 1 x VGA display port 1*HD OUTPUT display interface 2*RS232 serial port,COM1/2 supports 5V/12V power function,COM1/2 supports RS485/422 function 2*USB 2.0 ports 4*USB 3.0 ports 2*RJ-45 Gigabit network interface 1*Line out interface (green), 1*Mic interface (red)

Built-in I/O interface	1*JVGA port, 1*12pin row pin, same signal as external VGA 1*PS/2 keyboard and mouse interface 1*6pin row pins 1* front audio interface 2*5pin row pins 4*USB 2.0 port 2*5pin row pins 4 x RS232 serial port 2 x 20pin row pins 1* Front panel function buttons and indicator ports 2*5pin row pins 1*24pin ATX power input interface 1*4pin ATX power input interface 1*AC Power-on automatic power-on function 1*3pin row
Fan interface	1*4pin CPU intelligent fan interface, 1*4pin system intelligent fan interface
GPIO	Supports four input/output GPIO functions
BIOS	32Mb Flash ROM
Guard dog	Support hardware reset function (256 level, 0~255 seconds)
Operating system	Windows 7 / Linux
Power supply type	24Pin ATX power supply
Operating temperature	-10°C to 60°C
Storage temperature	-20°C to 70°C
Working humidity	5 ~ 90% relative humidity, no condensation
dimension	170mm x170mm (ITX)



深圳市汉智星科技有限公司

订购信息：

No.	Model	Processor	Southbridge	Memory	VGA	HD OUTPUT	LAN	USB	COM	RS485/422	Power
1	ITX-B75M1 VER:1.0	LGA1155	B75	1*DDR3	1	1	1*I211AT 1*I219V	10	6	COM1/COM2	ATX