



B76M3 VER:1.0 规格表



B76M3 VER:1.0 正面图



B76M3 VER:1.0 IO 图



B76M3 VER:1.0 侧面图



Product model	B76M3 VER:1.0
Processor	Supports LGA1155 architecture 2th/3th Intel® Celeron/Pentium/Core™ i3/i5/i7 processors
Chipset	Intel B75 high-speed chipset
Memory	2 x DDR3 DIMM slots for dual-channel 1066mhz, 1333mhz, or 1600 MHZ, supporting a maximum of 16GB
Reveal	Integrated Intel® HD Graphics controller with 1*VGA port and 1*HD OUTPUT1.4 port Supports single display mode, dual display mode, and extended mode
Network	2*Intel® WGI210AT Gigabit network adapter, supporting network wake up and PXE functions
Store	2*SATA 2.0 hard disk interface,SATA interface transmission speed up to 3Gbps 1*MSATA SSD interface, transmission speed up to 6Gbps
Audio frequency	Integrated ALC888S 7.1+2 hi-Fi audio controller, support Mic, Line out, line-IN
Expansion slot	1*PCIE x16
	1*PCIE x4
	2*PCI
	1*Mini-PCIE, WiFi support (optional TPM-4COM, can be expanded to 4 serial ports)
I/O ports on the backplane	1*PS/2 keyboard and mouse interface
	1 x VGA display port
	1*HD OUTPUT display interface
	2*RS232 serial port, COM1/2 supports 5V/12V power function, COM1/2 supports RS485/422 function
	2*USB 2.0 port
	4*USB 3.0 interface
	2*RJ-45 Gigabit network interface



	1*Line out interface (green), 1*MIC interface (red), 1* Line-IN interface (blue)
Built-in I/O interface	1*JVGA1 interface, 1*12pin row pin, same signal as external VGA
	1* PS/2 keyboard and mouse interface 1*6pin row pins
	1*LPT print port 2*13pin row pins
	1* front audio interface 2*5pin row pins
	4*USB 2.0 port 2*5Pin row pins
	1*USB2.0 port USB-TYPE A
	1* Front panel function buttons and indicator ports 2*5pin row pins
	1*24pin ATX power input interface
	2* 4pin ATX power input interface
Fan interface	1*4pin CPU intelligent fan interface, 2*4pin system intelligent fan interface
GPIO	Supports four input/output GPIO functions
BIOS	64Mb Flash ROM
Guard dog	Support hardware reset function (256 level, 0~255 seconds)
Operating system	Windows 7/Linux
Power supply type	24Pin ATX power supply
Operating temperature	-10°C to 60°C
Storage temperature	-20°C to 70°C
Working humidity	5 ~ 90% relative humidity, no condensation
Size	245mm x 220mm (mATX)



订购信息：

No.	Model	Processor	Chipset	Memory	VGA	HD OUTPUT	LAN	USB	COM	RS485/RS422	Power
1	B75M3 VER:1.0	LGA1155	B75	2*DDR3	1	1	1*I211AT 1*I219V	11	2	COM1/COM2	ATX
2	Q77M3 VER:1.0	LGA1155	Q77	2*DDR3	1	1	2*I210AT	11	2	COM1/COM2	ATX
3	B76M3 VER:1.0	LGA1155	B75	2*DDR3	1	1	2*I210AT	11	2	COM1/COM2	ATX