



研域
YENTEK

ITX-B305_I326L VER:1.0 规格表



ITX-B305_I326L VER:1.0 主板正面图



ITX-B305_I326L VER:1.0 主板 IO 图



ITX-B305_I326L VER:1.0 主板侧面图



Product model	ITX-B305_I326L VER:1.0(N305)
processor	Integrated Intel® Alder Lake-N Core I3-N305 3.8GHz octa-core eight-thread processor, TDP 15W, Compatible with the full range of Intel® Alder Lake-N cpus, customers can flexibly choose
chipset	SOC
Internal memory	1* SODIMM slot for a single channel of 3200MHz DDR4 memory (up to 16GB)
display	Integrated Intel® UHD Graphics core graphics card, support DirectX 12.1, OpenGL4.6 1*VGA,1*HD OUTPUT2.0 interface,1* LVDS interface,1* EDP interface, Note:LVDS and EDP interfaces are adaptive
network	2* RTL8111H Gigabit NIC, supports network wake up and PXE functions
Store	1* 7pin SATA3.0 hard disk interface, transmission rate up to 6Gbps 1* MSATA slot, support SSD SSD, SSD transfer speed up to 6Gbps 1 x M.2 slot, supporting the M.2 Key M 2280 PCIE X1 SSD
Tone frequency	Onboard ALC897 7.1+2 channel hi-fi audio controller with MIC/Line-out support. Power amplifier The power amplifier is recommended to use a 4 Ω 3W speaker
Expansion slot	1 x M.2 slot, supporting the M.2 Key B 2242/2252 5G module
I/O ports on the backplane	1* DC 12V power input port 1 * VGA display port 1* HD OUTPUT2.0 display interface 2* USB3.0 interface, 2* RJ45 Gigabit network interface 1* Line-out (green), 1*MICK(red)
Built-in I/O	1* DC power interface, 1*4pin support 12V power input and output



interface	1* JVGA port 1*12pin, same signal as DB15 1* LVDS interface, 2*15pin, support dual channel 24BIT, 1* EDP interface (yellow), 2*15pin, and LVDS for adaptive choice 1* screen backlight power supply interface 1*6pin 6* USB2.0 interface, 2*5pin 6* RS232 serial interface, COM1/2 support 9pin live function, COM2/COM3 support RS485/422 function, 1* hard drive power port 1*4pin 1* front audio interface 2*5pin 1* power amplifier interface 1*4pin 1* LPT interface 2*13pin 1* SIM card slot 1* Front panel function button and indicator port 2*5pin
Fan interface	1*4pin CPU intelligent fan interface, 1*4pin system fan interface
GPIO	Supports four input/output GPIO
BIOS	256Mb Flash ROM
Guard dog	Support hardware reset function (256 level, 0~255 seconds)
Operating system	Windows 10/Windows 11/Linux
Power supply type	Adopts DC 12V power supply
Operating temperature	-10°C to 60°C
Storage temperature	5%-95% relative humidity, no condensation
Working humidity	170mm * 170mm

订购信息：

保存期限：三年

表单编码：QR-PD-004 (A0)



NO.	Model	Processor	Frequency	Memory	VGA	HD OUTPUT	LVDS	EDP	LAN	USB	COM	485/422	Power
1	ITX-B305_I326L VER:1.0(N305)	I3-N305	3.8G	1*SODDR 4	1	1	2ch*24BIT	1	2*8I11H	8	6	COM2/3	DC12V
2	ITX-B305_I326L VER:1.0(N100)	N100	3.4G	1*SODDR 4	1	1	2ch*24BIT	1	2*8I11H	8	6	COM2/3	DC12V