



## ITX-B101\_C312L VER:1.0(5205U) 规格表



ITX-B101\_C312L VER:0.3 主板正面图



ITX-B101\_C312L VER:0.3 主板 IO 图



ITX-B101\_C312L VER:0.3 主板侧面图

Product number	ITX-B101_C312L VER:1.0(5205U)
processor	Integrated 10th generation Intel® Celeron 5205U 1.9GHz dual-core two-thread processor, TDP 15W Compatible with Intel® Comet Lake-U Celeron/Pentium/I3/I5/I7 low power processors
chipset	SOC
RAM	2*DDR4 SODIMM memory slots, support 2666MHz memory, up to 64GB
show	Integrated Intel® UHD Graphics, support DirectX 12 OpenGL 4.5, support 4K 1*VGA interface, the highest resolution supported is: 1920X1200@60Hz 1*HDMI1.4 interface, the highest resolution supported is: 4096x2304@24Hz 1*Support dual-channel 24bit LVDS interface, choose one from EDP, default LVDS
The internet storage	1* Intel I225 Gigabit LAN, support Wake-on-LAN, PXE function 1* SATA3.0 hard disk interface, the transmission speed can reach 6Gbps 1* MSATA slot, SSD solid state drive supporting Intel protocol, transmission speed up to 6Gbps 1* M.2 slot, support M.2 2260/2280 NVME PCIE x4 standard SSD Note: Choose either MSATA or TPM-4COM, you can use TPM-4COM to expand 4 serial ports, when using TPM-4COM small board, you can use M.2 SSD
audio	Integrated ALC892 7.1+2 channel high fidelity audio controller, support MIC, Line_out, power amplifier Support power amplifier 2 Ω 5W speaker
Expansion slot	1* Mini-PCIE slot, support WIFI/4G module
Backplane I/O Interface	2* USB3.0 interface, 2*USB2.0 interface 1* HDMI port 1* DB15 VGA port



1\* RJ45 Gigabit network interface  
1\*Line-out(green), 1\*MIC(red)  
1\* DC12V power interface, support 12V power input

Built-in I/O interface	1* JVGA1 interface 1*12pin (same signal as DB15) 1* JHDMI interface 2*10pin, same signal as HDMI interface 1* LVDS interface 2*15pin, support dual channel 24bit, 1* LVDS backlight power supply interface 1*6pin 1* Screen brightness adjustment interface 1*4pin 2* RS232 serial interface, COM1 supports the 9th pin live function, COM2 supports RS485/422 function, 1* PS/2 keyboard and mouse interface (red) 1*6Pin 4* USB2.0 interface 2*5pin , 1* Front audio interface 2*5pin 1* LPT printing interface 2*13pin 1* Front panel switch button and indicator port 2*5Pin 1* HDD power supply interface 1*4pin 1* Amplifier interface 1*4pin 1* 4pin ATX power interface (can be used as 12V input power interface) 1* SIM card holder
Fan interface	1*4pin CPU smart fan connector, 1* 4pin system fan connector
GPIO	Support 4-way input and output GPIO function
BIOS	128Mb Flash ROM
watchdog	Support hardware reset function (256 levels, 0~255 seconds)
Power Type	Powered by DC 12V power supply
operating system	Windows 10,/Linux
Operating temperature	-10°C ~ 60°C
Storage temperature	-20°C ~ 70°C
Working humidity	5%-95% relative humidity, no condensation



size

170mm x 170mm

## 订购信息

NO.	Model	Processor	Frequency	Memory	VGA	HDMI	LVDS	EDP	LAN	USB	COM	485	Power
1	ITX-B101_C312L VER:1.0(5205U)	5205U	1.9G	2*SODDR4	1	1	2ch/24Bit	/	1*I225	8	2	COM2	DC12V