



研域
YENTEK

H570S6 VER:1.0 规格表



H570S6 VER:1.0 主板正面图



H570S6 VER:1.0 主板 IO 图



H570S6 VER:1.0 主板侧面图



Product model	H570S6 VER:1.0
processor	Supports LGA1200 10th/11th Intel® Celeron/Pentium/Core™ i3/i5/i7/i9 processors, Note: Support 10/11 generation 125W CPU
chipset	Using Intel® Q570 chipset,
Internal memory	2 x DDR4 SODIMM slots, supporting a dual-channel memory of up to 3200MHz and up to 128GB
display	Integrated Intel®HD Graphics core graphics card supports DirectX12.1,OpenGL4.5, and supports 4K display
	1* DP interface. The maximum resolution is 1920X1200@60Hz
	1* HD OUTPUT1.4 interface, support the highest resolution of 4096x2304@24Hz
network	2* Intel ®I226V Gigabit network adapter chip, support network wake up /PXE function
store	6* SATA3.0 hard disk interface, transmission speed up to 6Gbps(Q570 Southbridge only supports 6 SATA, SATA7/8 is not available) 2* M.2 slot, support M.2 2280 NVME PCIE X4 standard SSD
Tone frequency	Onboard ALC897 7.1+2 channel hi-fi audio controller with MIC/Line-out support
Expansion slot	1* PCIE3.0 X16 slot
I/O ports on the backplane	1* TF card slot
	2* USB2.0 port
	1* DP interface
	1* HD OUTPUT port
	1* RJ45 serial port
	2* USB3.0 port
	2* RJ45 Gigabit network interface
	1* Line-out/MICK 2-in-1 audio interface
	1* Clear CMOS button



Built-in I/O interface	2* USB3.0 interface 2*10pin 2* USB2.0 interface 2*5pin 1* front audio interface 2*5pin 1* Network indicator port 1*4pin 1* Front panel function button and indicator port 2*5pin 1* 8pin ATX power interface 1* 20pin ATX power interface
Fan interface	1*4pin CPU fan interface; 2*4pin system fan port
GPIO	Supports four in four out GPIO function
BIOS	128Mb Flash ROM
Guard dog	Support hardware reset function (256 level, 0~255 seconds)
Operating system	Windows 10/Windows 11/Linux
Power supply type	Powered by ATX 20Pin and 8pin power supplies
Operating temperature	0°C to 60°C
Storage temperature	-20°C to 70°C
Working humidity	5%-95% relative humidity, no condensation
Size	170mm * 170mm

订购信息：

No.	Model	Processor	Frequency	Southbridge	Memory	VGA	HD OUTPU T	DP	LAN	USB	COM	RS485/422	Power
1	H570S6 VER:1.0	LGA1200	/	Q570	2*DDR4	/	1	1	2*I226V	8	1	/	ATX



研域
YENTEK

保存期限：三年

表单编码：QR-PD-004 (A0)